

Front Sprocket	Rear Sprocket	Ratio	Front Sprocket	Rear Sprocket	Ratio	% Change	RPM Change @ 6K	RPM Change @ 3.5K
20	60	3.00					6000	3500
20	61	3.05				1.7%	100	58
20	62	3.10				1.6%	98	57
20	63	3.15	19	60	3.16	1.6%	97	56
20	64	3.20	19	61	3.21	1.6%	95	56
20	65	3.25	19	62	3.26	1.6%	94	55
20	66	3.30	19	63	3.32	1.5%	92	54
20	67	3.35	19	64	3.37	1.5%	91	53
20	68	3.40	19	65	3.42	1.5%	90	52
20	69	3.45	19	66	3.47	1.5%	88	51
20	70	3.50				1.4%	87	51
20	71	3.55	19	67	3.53	1.4%	86	50
20	72	3.60	19	68	3.58	1.4%	85	49
20	73	3.65	19	69	3.63	1.4%	83	49
20	74	3.70	19	70	3.68	1.4%	82	48
20	75	3.75	19	71	3.74	1.4%	81	47
20	76	3.80	19	72	3.79	1.3%	80	47
20	77	3.85	19	73	3.84	1.3%	79	46
20	78	3.90	19	74	3.89	1.3%	78	45
20	79	3.95	19	75	3.95	1.3%	77	45
20	80	4.00	19	76	4.00	1.3%	76	44
20	81	4.05	19	77	4.05	1.3%	75	44
20	82	4.10	19	78	4.11	1.2%	74	43
20	83	4.15	19	79	4.16	1.2%	73	43
20	84	4.20	19	80	4.21	1.2%	72	42
20	85	4.25	19	81	4.26	1.2%	71	42
			19	82	4.32	1.2%	74	43
			19	83	4.37	1.2%	73	43
			19	84	4.42	1.2%	72	42
			19	85	4.47	1.2%	71	42